



## Description

**Fast drying pigmented high contrast printing ink for Continuous Ink Jet Applications.**

<b>Ink properties</b>	Excellent light fastness. Very good alcohol resistance. Very fast drying ink. Free of halogens.
<b>Adhesion</b>	Excellent adhesion on PVC materials. Very good adhesion on other plastic material.
<b>Colour</b>	Black





## Technical Data

<b>Recommended density</b>	<b>0,93 gcm-3</b>
<b>Nozzle</b>	75 - 52 $\mu$ m
<b>Frequency</b>	66 - 120 kHz

## Instruction

<b>Preparation</b>	Shake well before use.
<b>Printer adjustment</b>	Only use pigmented systems working with Ink care option.
<b>Make-up</b>	30153 / 80000

## Information

-  Shelf life: 12 months, store at temperatures between +10 and +30°C.
-  Observe your Material Safety Data Sheet as well as the instructions on the label.
-  Contains no aromatic solvents.
-  Resistance to "bleeding". No influence on the electrical characteristics. Pigments are free of lead and other heavy metal.

This technical information was made to the best of our knowledge after conscientious studies of all technical facts. Since specific application and handling of the products in the customer's plant are beyond our control, this company refuses in every respect the responsibility for injury and damage to man and material which may result from the use, stocking and application of our products. We emphasise that all our products are for industrial use only.